

AgriShift[®] TLUS Under-System Tube Light for Layers

- Noticeably calmer birds
- Brightens underneath cages
- Patent spectral output for avian vision
- Provides a uniform light pattern
- Significantly reduces floor eggs
- Reduces stress blood markers

Product shown with stringer—not included.



AgriShift° lighting systems "shift" spectrum and intensity, meeting the individual needs of your animals[†].



A **Built For Your Barn**° design uses materials that withstand harsh barn environments for years to come.

Animal-Centric Lighting Systems

The AgriShift^{*} TLUS under-system tube light provides layer producers with a lighting solution that brightens underneath cages to significantly reduce floor eggs. This 5 foot in-system lighting option provides a uniform and continuous light pattern free of dark spots and shadows s birds are less likely to lay eggs under the caging systems, while being noticeably calmer.

Improves Animal Welfare

The AgriShift^{*} TLUS is fully dimmable, minimizing extreme changes in lighting. Abrupt changes are shown to excite flight responses, increasing cortisol levels and inhibiting melatonin secretion—both of which have a negative effect on the wellbeing of the bird. With uniform coverage and a consistent light pattern with slow ramping, corticosterone levels and other stress markers are minimized, improving animal welfare.



Patent spectral output for avian vision. Pat. www.once.lighting/patents and Other Worldwide Patents Pending Copyright © 2020 by ONCE' Revised January 2020

www.once.lighting layers@onceteam.com • 15255 23rd Avenue North, Plymouth, MN 55447 • T +1 (763) 381-5621 - Ext. 2

AgriShift[®] TLUS Specifications

Nominal Power	1-Tube Assembly: 8W (at full intensity)	
Luminous Flux	470 lm human photopic	
Input Voltage	120 VAC* / 50/60 Hz	
Beam Angle	200°	
Light Output Equivalence	Up to 40W incandescent	
Spectral Output	Species-specific blue/green enhanced white	
Operating Temperature	-20°C to 40°C / -4°F to 104°F	
Dimmable Range	100% to 5%, dims to blue-white moonlight	
Dimmer Type	Phase Modulation or Amplitude Control*	
Environmental Ratings	Suitable for damp locations ^{**} , Suitable for Indoor corrosive environments per UL50E Salt Spray Test, RoHS Compliant	
Safety	Conforms to ANSI/UL STD 1598, Certified to Can/CSA STD. C22.2 NO. 250.0	
Rated Life	50,000 hours	

Ordering Information

AgriShift [®] TLUS	SKU			
1-Tube Assembly, 60" OAL	TLUS-0164-1-120 (24-0164)			
Includes mounting clips, female connector one end				
1-Tube Assembly, 60" OAL	TLUS-0165-1-120 (24-0165)			
With Dim-to-Blue® technology				
Includes mounting clips, female con	nnector one end			
AgriShift [®] TLUS Accessories	SKU			
AgriShift [®] TLUS Stringer, 88 ft	TLUS-24-0167			
Includes 10 connectors				
AgriShift [®] TLUS Lead Wire Kit, 4 ft	TLUS-24-0168			


Includes starter cord and end cap		
AgriShift [®] Controllers	SKU	
AgriShift [®] G Controller	ALC-G2S-UNAC-2-10	
AgriShift [®] Master Controller 120V	30-014-00188-L123	
AgriShift [®] Slave Dimmer 120V	30-014-00189-L123	
AgriShift [®] Master Controller 240V-50Hz	30-014-00180-L123	
AgriShift [®] Master Controller 240V-60Hz	30-014-00180-L123-60Hz	

For optimum dimming performance use AgriShift Controllers **May not meet electrical codes in all states

AgriShift[®] TLUS Mechanical Dimensions



AgriShift[®] TLUS Stringer Mechanical Dimensions



Complete Your AgriShift[®] Lighting System: AgriShift[®] G Controller

- Improves animal welfare
- Offers several advanced features, adding flexibility
- Eliminates lighting anomalies to increase production
- Universal input power

The AgriShift^{*} G Controller is a slave dimmer that provides full potential to any ONCE^{*} AC lighting fixture. It offers smooth dimming solutions that can easily be controlled by two separate 0-10 VDC control signals and several advanced features, giving added flexibility while addressing the complex needs of today's modern agriculture facilities.



Reliable3601-888-218-7829sales@ruby360.caIntegrated Agricultural Solutions40 Woodstock St. N., Tavistock, ON NOB 2R0

on NOB 2R0 ruby360.ca ONCE